

SUSANA MARTINEZ Governor JOHN A. SANCHEZ Lieutenant Governor

NEW MEXICO ENVIRONMENT DEPARTMENT

Harold Runnels Building
1190 South St. Francis Drive (87505)
P.O. Box 5469, Santa Fe, NM 87502-5469
Phone (505) 827-0187 Fax (505) 827-0160
www.nmenv.state.nm.us



RYAN FLYNN Cabinet Secretary BUTCH TONGATE Deputy Secretary

Certified Mail - Return Receipt Requested

July 22, 2016

Mr. Fernando Garcia, Mayor Town of Springer Post office Box 488 Springer, New Mexico 87747

RE: Minor Industrial, SIC 4941, NPDES Compliance Evaluation Inspection, Town of Springer Water Treatment Plant, NM0030627, July 7, 2016

Dear Mr. Garcia:

Enclosed please find a copy of the report and check list for the referenced inspection that the New Mexico Environment Department (NMED) conducted at your facility on behalf of the U.S. Environmental Protection Agency (USEPA). This inspection report will be sent to the USEPA in Dallas for their review. These inspections are used by USEPA to determine compliance with the National Pollutant Discharge Elimination System (NPDES) permitting program in accordance with requirements of the federal Clean Water Act.

You are encouraged to review the inspection report, required to correct any problems noted during the inspection, and advised to modify your operational and/or administrative procedures, as appropriate. If you have comments on or concerns with the basis for the findings in the NMED inspection report, please contact us (see the address below) in writing within 30 days from the date of this letter. Further you are encouraged to notify in writing both the USEPA and NMED regarding modifications and compliance schedules at the addresses below:

Racquel Douglas US Environmental Protection Agency, Region VI Enforcement Branch (6EN-WM) Fountain Place 1445 Ross Avenue Dallas, Texas 75202-2733 Bruce Yurdin
New Mexico Environment Department
Surface Water Quality Bureau
Point Source Regulation Section
P.O. Box 5469
Santa Fe, New Mexico 87502

If you have any questions about this inspection report, please contact Sandra Gabaldon at (505) 827-1041 or at sandra.gabaldon@state.nm.us.

Sincerely,

/s/ Bruce J. Yurdin

Bruce J. Yurdin Program Manager Point Source Regulation Section Surface Water Quality Bureau

cc: Carol Peters-Wagnon, USEPA (6EN-WM) by e-mail Racquel Douglas, USEPA (6EN-WM) by e-mail Gladys Gooden-Jackson (6EN-WC) by e-mail Brent Larsen, USEPA (6WQ-PP) by e-mail

NMED District II, Robert Italiano, Manager, by e-mail



Form Approved OMB No. 2040-0003 Approval Expires 7-31-85

	Section A: National Data System Coding																														
	Transaction Code NPDES yr/mo/day Inspec. Type Inspector Fac Type																														
1 N 2 5 3 N M 0 0 3 0 6				2	7	11	12		1 6	۰	71711107 7	0 ay	7	17	18	c	he	19	specia	20	1 1	3									
			<u> </u>		<u> </u>	1	L 			1	1 -	<u> </u>	<u> </u>	<u> </u>	<u>-</u> ! .1	ı	L	<u> </u>	 	1	 	<u> </u>] 	Ī	انا	ı	· .		! 		
Į.	W	Α	T	E	R			Т	R	E	Α	T	M	E	N	T	1]		<u> </u>							
		pecti	on \ 	Vork I	T				Fa	•	Evalua	tion F	kating	J	71	BI N	1.	QA 72 N	73	1	 	 ₇₁	 7E	 	Reserve	ed 		 	 	 _{on}	
	67		<u> </u>		69					70	3	J			71	N		72 N	/ /3	<u>L</u>		74	75						<u> </u>	80	
	Section B: Facility Data																														
include POTW name and NPDES permit number) Town of Springer Water Treatment Facility From I-25 N, take exit 412, continue ~0.9 miles on Maxwell Avenue, then 0.3 miles on									embe	r 1, 2	e Dat 2013 on Da																				
	road / ited oi				est on	NM ·	468	s, tra	vel 1	.9 mile	es, turr					d. Fa	cilit	LV I	xit Tin 200 F			7, 2016	5			ber 3			ale		
Nar	ne(s)	of On	-Ci+	a Ron	racan	tativo	2(6)	/Ti+l-	2/61/5	Phone	and Fa			OUNT	Υ									Oth	ner Faci	ility D	ata				_
											tos_w				m											,	aia				
Name, Address of Responsible Official/Title/Phone and Fax Number Mr. Fernando Garcia, Mayor / (575) 483-2682 / (575) 483-2910 Contacted Yes No * Outfall 001: Latitude N. 36. Longitude W SIC 4941 SIC 4941							. 36.3			0°																					
	Section C: Areas Evaluated During Inspection (S = Satisfactory, M = Marginal, U = Unsatisfactory, N = Not Evaluated)																														
s								erations & Maintenance N			CSO/SSO				٦																
M	Re	cord	s/Re	ports	;			5	3	Self-	Monit	oring) Pro	 			Sludg	ludge Handling/Disposal N				Pollution Prevention									
s	Fac	cility	Site	Revi	ew			١	1	Com	plianc	e Scł	nedules N Pr			Pretre	Pretreatment			N	Multimedia										
N	Eff	luent	/Re	ceivir	ıg Wa	ters		ι	J	Labo	ratory			N Storm Water N					N	Other:											
								s	ectio	on D:	Summ	ary o	of Fir	dings	s/Con	nmen	ts ((Attach	addit	ional	sheet	s if ne	cessa	ary)							
	Please see checklist and further explanations for details of findings																														
	me(s) / San				e(s) o	f Ins	pec	tor(s)				Ag	ency	Office	e/Tel	eph	none/Fa	x						Date						
	dra G												NI	IED/S	WQB	/(505) 82	27-104 ⁻	/(505)	827-	0160				07/22/2016						
					nent C	A Re	evie	ewer					Ag	ency	Office	e/Pho	one	and F	x Nu	nbers	- <u>-</u>				Date						
	s/ <i>Bruce Yurdin</i> for ennifer Foote, Municipal Team Lead							NN	IED/S	WQB	/(505	82	27-0596	/(505)	827-	0160				07/22/2016											

SECTION A – PERMIT VERIFICATION PERMIT SATISFACTORILY ADDRESSES OBSERVATIONS X S M U NA (FURTHER EXPLANATION ATTACHED NO) DETAILS: The Permit is issued to "City of Springer Water Treatment Plant". The correct name is "Town of Springer" 1. CORRECT NAME AND MAILING ADDRESS OF PERMITTEE Y X N 2. NOTIFICATION GIVEN TO EPA/STATE OF NEW DIFFERENT OR INCREASED DISCHARGES O Y N	
DETAILS: The Permit is issued to "City of Springer Water Treatment Plant". The correct name is "Town of Springer" 1. CORRECT NAME AND MAILING ADDRESS OF PERMITTEE Y X N	
1. CORRECT NAME AND MAILING ADDRESS OF PERMITTEE "YXN	
2. NOTIFICATION GIVEN TO EPA/STATE OF NEW DIFFERENT OR INCREASED DISCHARGES O Y N	× ΝΔ
	7 101
3. NUMBER AND LOCATION OF DISCHARGE POINTS AS DESCRIBED IN PERMIT X Y N	NA NA
4. ALL DISCHARGES ARE PERMITTED X Y Y N	NA
SECTION B – RECORDKEEPING AND REPORTING EVALUATION	
RECORDS AND REPORTS MAINTAINED AS REQUIRED BY PERMIT. OSXM UNA (FURTHER EXPLANATION ATTACHED YES) DETAILS:	
1. ANALYTICAL RESULTS CONSISTENT WITH DATA REPORTED ON DMRs. Y N	 NA
2. SAMPLING AND ANALYSES DATA ADEQUATE AND INCLUDE. OS " M " U	·· NA
a) DATES, TIME(S) AND LOCATION(S) OF SAMPLING O Y X N	ı NA
b) NAME OF INDIVIDUAL PERFORMING SAMPLING X Y N	ı NA
c) ANALYTICAL METHODS AND TECHNIQUES.	J NA
d) RESULTS OF ANALYSES AND CALIBRATIONS. X Y N	ı NA
e) DATES AND TIMES OF ANALYSES. X Y N	ı NA
f) NAME OF PERSON(S) PERFORMING ANALYSES. X Y N	N NA
3. LABORATORY EQUIPMENT CALIBRATION AND MAINTENANCE RECORDS ADEQUATE. X S M U	J NA
4. PLANT RECORDS INCLUDE SCHEDULES, DATES OF EQUIPMENT MAINTENANCE AND REPAIR. OSX M. U	NA
5. EFFLUENT LOADINGS CALCULATED USING DAILY EFFLUENT FLOW AND DAILY ANALYTICAL DATA. O Y N	X NA
SECTION C – OPERATIONS AND MAINTENANCE	
TREATMENT FACILITY PROPERLY OPERATED AND MAINTAINED. S X M U NA (FURTHER EXPLANATION ATTACHED YES) DETAILS:	
1. TREATMENT UNITS PROPERLY OPERATED. X S " M O L	J NA
2. TREATMENT UNITS PROPERLY MAINTAINED. X S M OU	·· NA
3. STANDBY POWER OR OTHER EQUIVALENT PROVIDED . X S M U	л NA
4. ADEQUATE ALARM SYSTEM FOR POWER OR EQUIPMENT FAILURES AVAILABLE. X S MOU	J NA
5. ALL NEEDED TREATMENT UNITS IN SERVICE X S MO	U ·· NA
6. ADEQUATE NUMBER OF QUALIFIED OPERATORS PROVIDED. S X M OU	J NA
7. SPARE PARTS AND SUPPLIES INVENTORY MAINTAINED. X S M U	U NA
8. OPERATION AND MAINTENANCE MANUAL AVAILABLE. X Y N STANDARD OPERATING PROCEDURES AND SCHEDULES ESTABLISHED. X Y O N PROCEDURES FOR EMERGENCY TREATMENT CONTROL ESTABLISHED. OY X N	N NA

TOWN OF SPRINGER WATER TREATMENT PLANT	PERMIT NO. NM30627
SECTION C – OPERATIONS AND MAINTENANCE (CONT'D)	
9. HAVE BYPASSES/OVERFLOWS OCCURRED AT THE PLANT OR IN THE COLLECTION SYSTEM IN THE LAST YEAR? IF SO, HAS THE REGULATORY AGENCY BEEN NOTIFIED? HAS CORRECTIVE ACTION BEEN TAKEN TO PREVENT ADDITIONAL BYPASSES/OVERFLOWS?	OYXN NA OY NX NA OYONX NA
10.HAVE ANY HYDRAULIC OVERLOADS OCCURRED AT THE TREATMENT PLANT? IF SO, DID PERMIT VIOLATIONS OCCUR AS A RESULT?	Y X N NA Y N X NA
SECTION D – SELF-MONITORING	
PERMITTEE SELF-MONITORING MEETS PERMIT REQUIREMENTS. X S M U NA (FURTHER EXP. DETAILS:	PLANATION ATTACHED <u>NO</u>).
1. SAMPLES TAKEN AT SITE(S) SPECIFIED IN PERMIT.	X Y N NA
2. LOCATIONS ADEQUATE FOR REPRESENTATIVE SAMPLES.	X Y N NA
3. FLOW PROPORTIONED SAMPLES OBTAINED WHEN REQUIRED BY PERMIT.WET testing 24-hour composite. Once per permit tertaken.	
	O Y " N X NA
4. SAMPLING AND ANALYSES COMPLETED ON PARAMETERS SPECIFIED IN PERMIT.	X Y N NA
5. SAMPLING AND ANALYSES PERFORMED AT FREQUENCY SPECIFIED IN PERMIT.	X Y N NA
6. SAMPLE COLLECTION PROCEDURES ADEQUATE	X Y NA
a) SAMPLES REFRIGERATED DURING COMPOSITING.	X Y NA
b) PROPER PRESERVATION TECHNIQUES USED.	X Y N NA
c) CONTAINERS AND SAMPLE HOLDING TIMES CONFORM TO 40 CFR 136.3.	X Y N NA
7. IF MONITORING AND ANALYSES ARE PERFORMED MORE OFTEN THAN REQUIRED BY PERMIT, ARE THE RESULTS REPORTED IN PERMITTEE'S SELF-MONITORING REPORT?	O Y ·· N X NA
SECTION E – FLOW MEASUREMENT	
PERMITTEE FLOW MEASUREMENT MEETS PERMIT REQUIREMENTS. X S M U NA (FURTHER EXPLIDETAILS: Permit requires an "estimate" effluent flow be reported.	LANATION ATTACHED <u>NO</u>)
PRIMARY FLOW MEASUREMENT DEVICE PROPERLY INSTALLED AND MAINTAINED. TYPE OF DEVICE <u>Estimate Flow</u>	X Y N NA
2. FLOW MEASURED AT EACH OUTFALL AS REQUIRED.	OY"NXNA
3. SECONDARY INSTRUMENTS (TOTALIZERS, RECORDERS, ETC.) PROPERLY OPERATED AND MAINTAINED.	OY"NXNA
4. CALIBRATION FREQUENCY ADEQUATE. RECORDS MAINTAINED OF CALIBRATION PROCEDURES. CALIBRATION CHECKS DONE TO ASSURE CONTINUED COMPLIANCE.	O Y N X NA O Y N X NA O Y N X NA
5. FLOW ENTERING DEVICE WELL DISTRIBUTED ACROSS THE CHANNEL AND FREE OF TURBULENCE.	O Y N X NA
6. HEAD MEASURED AT PROPER LOCATION.	OY"NXNA
7. FLOW MEASUREMENT EQUIPMENT ADEQUATE TO HANDLE EXPECTED RANGE OF FLOW RATES.	O Y N X NA
SECTION F - LABORATORY	
PERMITTEE LABORATORY PROCEDURES MEET PERMIT REQUIREMENTS. O S " M X U " NA (FURTHER EXPLIDETAILS:	LANATION ATTACHED <u>YES)</u>
1. EPA APPROVED ANALYTICAL PROCEDURES USED (40 CFR 136.3 FOR LIQUIDS, 503.8(b) FOR SLUDGES)	O Y X N NA

	PERMIT NO	PERMIT NO. NM30627							
SECTION F - LABORATORY (CONT'D)									
2. IF ALTERNATIVE	ANALYTICAL PROCED	OURES ARE USED, PRO	PER APPROVAL HAS B	EEN OBTAINED		y N >	(NA		
3. SATISFACTORY C	CALIBRATION AND MA	INTENANCE OF INSTR	UMENTS AND EQUIPM	IENT.		X S O M U NA			
4. QUALITY CONTR	OL PROCEDURES ADE	QUATE.				O S M X U	NA		
5. DUPLICATE SAMI	5. DUPLICATE SAMPLES ARE ANALYZED. <u>0</u> % OF THE TIME. O Y X N NA								
6. SPIKED SAMPLES ARE ANALYZED. 0 % OF THE TIME. "Y X N O NA									
7. COMMERCIAL LA	7. COMMERCIAL LABORATORY USED. X Y N NA								
LAB NAME	Hall Environmental		Rato	n Waterwater Treatment F	Facility Laboratory				
LAB ADDRESS	4901 Hawkins, NE; Su	nite D; Albuquerque, NM	87109 420 1	Hereford Avenue; Raton,	NM 87740				
PARAMETERS PER	RFORMED <u>Total Alum</u>	inum; Copper, Nickel, Zir	nc TSS						
SECTION G - EFI	FLUENT/RECEIVIN	G WATERS OBSER	VATIONS. O	s M O II X NA	A (FURTHER EXPLANATIO	ON ATTACHED NO)			
OUTFALL NO.	SECTION G - EFFLUENT/RECEIVING WATERS OBSERVATIONS. O S M O U X NA (FURTHER EXPLANATION A OUTFALL NO. OIL SHEEN GREASE TURBIDITY VISIBLE FOAM FLOAT SOL.								
001	NO DISCHARGE	NO DISCHARGE	NO DISCHARGE	NO DISCHARGE	NO DISCHARGE	NO DISCHARGE			
RECEIVING WATER	OBSERVATIONS N	o discharge during inspect	ion.						
SECTION H - SLU	DGE DISPOSAL								
	. MEETS PERMIT REQU catment Plant – No sludge			s m n X N	A (FURTHER EXPLANATI	ON ATTACHED <u>NO</u>).			
1. SLUDGE MANAG	GEMENT ADEQUATE TO) MAINTAIN EFFLUEN	Г QUALITY.			_S _M _U	NA		
2. SLUDGE RECORI	DS MAINTAINED AS RE	EQUIRED BY 40 CFR 50	3.			_S _M _U	NA		
3. FOR LAND APPL	IED SLUDGE, TYPE OF	LAND APPLIED TO: <u>N</u>	/A (e.g., FOREST, AGF	RICULTURAL, PUBLIC	CONTACT SITE)				
SECTION I - SAM	MPLING INSPECTIO	ON PROCEDURES	(FURTHER EXPLANATION	ATTACHED).					
1. SAMPLES OBTAI	NED THIS INSPECTION	1.				Y N 2	X NA		
2. TYPE OF SAMPLI	E OBTAINED								
GRAB COMPOSITE SAMPLE METHOD FREQUENCY									
3. SAMPLES PRESERVED. Y N NA									
4. FLOW PROPORTIONED SAMPLES OBTAINED. Y N NA									
5. SAMPLE OBTAINED FROM FACILITY'S SAMPLING DEVICE. Y N NA									
6. SAMPLE REPRES	6. SAMPLE REPRESENTATIVE OF VOLUME AND MATURE OF DISCHARGE.								
7. SAMPLE SPLIT W	/ITH PERMITTEE.					_Y _N .	NA		
8. CHAIN-OF-CUST	ODY PROCEDURES EM	PLOYED.				_Y _N	. NA		
9. SAMPLES COLLE	9. SAMPLES COLLECTED IN ACCORDANCE WITH PERMIT. "Y"N NA								

Town of Springer Water Treatment Facility

NPDES Permit No.: NM0030627 Compliance Evaluation Inspection Date of Inspection: July 7, 2016

Introduction:

On July 7, Sandra Gabaldón accompanied by Daniel Valenta, both of the New Mexico Environment Department (NMED), Surface Water Quality Bureau (SWQB) conducted a Compliance Evaluation Inspection (CEI) at the Town of Springer Water Treatment Plant (WTP). The Town of Springer WTP has a design flow capacity of 0.28 MGD (million gallons per day) and is classified as a minor industrial discharger under the federal Clean Water Act, Section 402, of the National Pollutant Discharge Elimination System (NPDES) permit program. It is assigned NPDES permit number NM0030627, which regulates discharge of treated backwash water from outfall 001 to an unnamed tributary, thence to the Cimarron River in Segment 20.6.4.306 State of New Mexico Standards for Interstate and Intrastate Surface Waters, 20.6.4 New Mexico Administrative Code (NMAC). This segment includes the designated uses of irrigation, warmwater aquatic life, livestock watering, wildlife habitat and primary contact.

The NMED performs a certain number of CEIs for the U.S. Environmental Protection Agency (USEPA), Region VI, under the NPDES permit program, in accordance with the federal Clean Water Act. USEPA uses these inspections to determine compliance with the NPDES permit program. This inspection report is based on information provided by the permittee's representatives, observations made by the NMED inspector, and records and reports kept by the permittee and/or NMED.

Upon arrival at the Town of Springer Administrative offices at approximately 0920 hours, the inspectors met Ms. Laura Danielson, Water Supervisor. During the entrance interview, the inspector presented her credentials, made introductions and explained the purpose of the inspection. A review of records from previous discharges was done prior to touring the water treatment plant and the newly remodeled dam.

A tour of the facility commenced after review of records. Ms. Danielson was unable to tour the facility with the inspectors due to an illness. Ms. Danielson waited in the WTP until the inspectors completed the tour. An exit interview with Ms. Danielson was held on-site after the inspection at approximately 1245 hours.

Treatment Scheme:

The Town of Springer WTP treats surface water from a reservoir on site. The facility serves a population of approximately 1,047 (US Census 2010) and the Springer Correctional Facility. The

reservoir has a spillway and associated drainage ditch leading toward the unnamed tributary south of the facility.

Raw water from the lower reservoir flows via gravity to a pump station and sent to the enclosed treatment plant. Raw water is treated by two Tonka package plants rated at 525,600 gallons per day each. Treatment processes are conventional and include coagulation, flocculation, sedimentation, filtration and disinfection. The treatment scheme consists of chemical injection followed by two parallel package units, each compartmentalized into two flocculation chambers, sedimentation basin, and multi-media filter. Depending on water demand or maintenance schedule, one or both of the package units may be placed into service at any time. Following filtration, water is disinfected with a MIOX disinfecting solution before distribution to the drinking water system.

At the head of the plant, aluminum sulfate and cationic polymer (poly diallyldimethylammonium chloride or pDADMAC) are injected into the raw water within the intake pipes and then flash mixed. Water flows into the flocculation chamber where horizontal paddle wheel mixers enhance the coagulation-flocculation process. Following the flocculation chamber, flow enters the sedimentation basin and is thrust up through tube settlers. The upward movement of water through the tube settlers allows each tube to function as a small settling basin. From the sedimentation basin, water enters a multi-media filtration unit for removal of remaining suspended solids. Filter backwashing begins automatically at a preset interval based on continuously monitored effluent turbidity levels. The operator may also manually backwash the filter media. Finished water is used to backwash the filters. Backwash water is flushed to a detention pond adjacent to the treatment building.

Prior to disinfection, emergency overflows from the package plant also flow to the backwash pond. Floor drains inside the treatment plant also flow to the backwash pond.

Further Explanations:

Note: The sections are arranged according to the format of the enclosed EPA Inspection Checklist (Form 3560-3), rather than being ranked in order of importance.

<u>Section A - Permit Verification – Overall Rating of "Satisfactory":</u>

This is only a comment:

On review of the permit issued on November 1, 2013 with an expiration date of October 31, 2018, the name of the facility is "City of Springer Water Treatment Plant". The correct name of the facility is "Town of Springer Water Treatment Plant".

Section B – Recordkeeping and Reporting – Overall Rating of "Marginal"

The permit requires, in part III.C.4, Records Contents:

Records of monitoring information shall include:

- a. The date, exact place, and time of sampling or measurements;
- b. The individual(s) who performed the sampling or measurements;
- c. The date(s) and time(s) analyses were performed;
- d. The individual(s) who performed the analyses;
- e. The analytical techniques or methods used; and
- f. The results of such analyses.

The permit requires, in part II.B.2, 24-Hour Oral Reporting: Daily Maximum Limitation Violations:

Violations of daily maximum limitations for the following pollutants shall be reported orally to NMED only, within 24 hours from the time the permittee becomes aware of the violation followed by a written report within five days.

Total Aluminum Total Residual Chlorine

<u>Findings</u> for Recordkeeping and Reporting:

The permittee has failed to provide the analytical technique being used for the analysis of Dissolved Oxygen (DO).

The permittee also has an analytical technique stated for Total Residual Chlorine (TRC) as "8067". This method is **not** an approved method under 40 CFR 136. Approved methods under 40 CFR 136 include:

Chlorine-Total residual, mg/L	Amperometric direct	4500-CI D-2000	D1253-08
	Amperometric direct (low level)	4500-CI E-2000	
	lodometric direct	4500-CI B-2000	
	Back titration ether end-point ¹⁵	4500-CI C-2000	
	DPD-FAS	4500-CI F-2000	
	Spectrophotometric, DPD	4500-CI G-2000	
	Electrode		

The permittee has two contract laboratories. The permittee uses Raton Wastewater Treatment Plant Laboratory for analysis of Total Suspended Solids (TSS). They are required to monitor once per week when discharging. The permittee does not have Chain of Custody (COC) records for samples taken to Raton. The COC is used to verify the validity of the sample. Written records need to be provided to trace the custody of each sample. Included in the COC are signatures of the transferee (contract laboratory) the date and time, condition of the sample, and preservation technique used. The permittee should have COCs for every group or individual sample transferred to any person.

The permittee had an exceedance of Total Aluminum in January 2016. The permit limitation is 2.6 daily maximum. The permittee reported on NetDMR the results for Total Aluminum was 5.0 mg/L daily maximum. The permittee failed to notify NMED either in writing or telephone for this exceedance.

Section C - Operation and Maintenance - Overall Rating of "Satisfactory"

The permit requires in Part III, B.3 Proper Operation and Maintenance:

- a. The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by permittee as efficiently as possible in a manner which will minimize upsets and discharges of excessive pollutants and in will achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls and appropriate quality assurance procedures. This provision requires the operation of backup or auxiliary facilities or similar systems which are installed by a permittee only when the operation is necessary to achieve compliance with the conditions of this permit.
 - b. The permittee shall provide an adequate operating staff which is duly qualified to carry out operation, maintenance and testing functions required to insure compliance with the conditions of this permit.

<u>Findings</u> for Operation and Maintenance:

The permittee does not have an emergency treatment plan in place at the facility.

The operator stated that she, Laura Danielson, plans to retire in the near future. This facility has only one certified operator. The Springer WTP needs to employ at least two certified operators to operate the facility and remain in compliance with the permit.

<u>Section F – Laboratory – Overall Rating of "Unsatisfactory"</u>

In Part III, Section C. 5, Monitoring Procedures:

- a. Monitoring must be conducted according to test procedures approved under 40 CFR Part 136, unless other test procedures have been specified in this permit or approved by the regional administrator.
- b. The permittee shall calibrate and perform maintenance procedures on all monitoring and analytical instruments at intervals frequent enough to insure accuracy of measurements and shall maintain appropriate records of such activities.
- c. An adequate analytical quality control program, including the analyses of sufficient standards, spikes and duplicate samples to insure the accuracy of all required analytical results shall be maintained by the permittee or designated commercial laboratory.

Findings for Laboratory:


The permittee is not using 40 CFR Part 136 approved methodology for Total Residual Chlorine. The bench sheets reviewed state method "8067" is being used to analyze TRC.

The permittee is not doing duplicate samples at least 10% of the time to verify precision of the laboratory.


Photographer: Daniel Valenta	Date: July 7, 2016	Time: 1015 Hours				
City/County: Town of Springer / Colfa	ax County	State: New Mexico				
Location: Town of Springer Water Treatment Plant						
Subject: Unlined backwash pond						



Photographer: Daniel Valenta	Date: July 7, 2016	Time: 1027 Hours				
City/County: Town of Springer / Colfa	x County	State: New Mexico				
Location: Town of Springer Water Treatment Plant						
Subject: Discharge pipe from backwash pond						



Photographer: Daniel Valenta	Date: July 7, 2016	Time: 1041 Hours				
City/County: Town of Springer / Colfa	State: New Mexico					
Location: Town of Springer Water Treatment Plant						
Subject: Overview of rehabilitated dam						



Photographer: Daniel Valenta	Date: July 7, 2016	Time: 1046 Hours				
City/County: Town of Springer / Colfa	x County	State: New Mexico				
Location: Town of Springer Water Treatment Plant						
Subject: Overview of spillway						

